

JETTA BRAKE FLUID DOT 4

Heavy-Duty Synthetic Brake & Clutch Fluid · DOT 4

DESCRIPTION

A heavy-duty synthetic brake and clutch fluid which meets the requirements of the latest issue of US FMVSS 116 DOT 4, SAE J1704 and ISO 4925 (Classes 3 & 4) specifications.

APPLICATION

Suitable for all hydraulic brake systems with drum or disc brakes requiring a synthetic brake fluid where a DOT 4 type fluid is prescribed.

BENEFITS

- Good resistance against ageing
- Very good compatibility with seals and gaskets
- Minimal corrosion tendency
- High wet boiling point
- Optimal viscosity at low temperatures

PERFORMANCE LEVELS

- US FMVSS 116 DOT 4
- SAE J1704
- ISO 4925 (Classes 3 & 4)

PACK SIZES

Multiple pack sizes available on request.

PHYSICAL PROPERTIES

PROPERTY	TEST METHOD	UNIT	TYPICAL VALUE
Density at 15/4 °C	ASTM D-1298 / IP 160	kg/L	1.06
Kinematic viscosity at -40 °C	ASTM D-445 / IP 71	cSt	1800 max
Kinematic viscosity at 100 °C	ASTM D-445 / IP 71	cSt	1.5 min
Colour	Visual	-	Colourless to amber
Equilibrium reflux boiling point, dry	-	°C	230 min
Equilibrium reflux boiling point, wet	-	°C	155 min
Water content	ASTM D-1364 / D-6304	%wt	0.2 max
pH	ASTM D-1121	-	7.0 - 11.5

Typical values shown do not constitute a specification. The information is based on current knowledge and is intended to describe the product for possible applications; it does not release the user from performing preliminary tests.