

JEMATIC ATF VI

Low-Viscosity Automatic Transmission Fluid · DEXRON VI

DESCRIPTION

100% Synthetic High performance low viscosity lubricant specially engineered for modern automatic transmission (manual mode, sequential mode, electronically controlled) with or without slip lockup clutch requiring a DEXRON VI fluid.

FEATURES

- Reliable and consistent shift performance
- Long service life (twice the service interval of Dexron IIIH)
- Stable high temperature performance
- Combats sludge and varnish build up
- Maintains gear integrity and optimises efficiency
- Outstanding low temperature fluidity
- Superior oxidation and thermal stability control

PACK SIZES

Multiple pack sizes available on request.

APPLICATIONS

- Modern automatic transmissions (manual mode, sequential mode, electronically controlled) with or without slip lockup clutch requiring a DEXRON VI fluid

PRODUCT CHARACTERISTICS

PROPERTY	TYPICAL VALUE
Specification / approval	GM DEXRON VI
Specification / approval	MB 236.41
Specification / approval	FORD MERCON LV
Specification / approval	ALLISON C4
Specification / approval	VOITH H55.6335xx

Typical values shown do not constitute a specification. The information is based on current knowledge and is intended to describe the product for possible applications; it does not release the user from performing preliminary tests.