

TECHNICAL DATA SHEET

RUSTOVEL A114

FLASH POINT

>180 °C

SALT SPRAY TEST

>24 hours

VISCOSITY 40 °C

2-4 cSt

DENSITY 15 °C

0.88 kg/L

DESCRIPTION

RUSTOVEL A114 is a corrosion-preventive and antirust oil that is not washed off by water. It provides outstanding rust protection for 12 months and can be removed by washing with solvent.

FEATURES AND BENEFITS

Spreadability

- High penetration and spreadability, covering large areas.

Film Stability

- Thixotropic properties of the oil provide high film stability.

Resistance to Water

- Excellent resistance to water washout and spray-off.

Anti-Wear Properties

- Anti-wear properties provide protection against premature wear.

Corrosion Resistance

- High corrosion-inhibiting properties protect components stored in very humid environments.

Resistance to Oxidation

- The use of a premium antioxidant ensures excellent thermal and oxidation stability.

APPLICATION AREAS

Steel sheets, equipment, tools.

TYPICAL DATA

TEST	RESULT
Colour	Yellowish brown
pH	6-7
Kinematic viscosity at 40 °C	2-4 cSt
Density at 15 °C, ASTM D1298	0.88 kg/L
Flash Point	>180 °C
Rust test, ASTM D665 B (synthetic sea water)	Pass
Salt spray test, ASTM B117	>24 hours